



AUMSHIVAY ENGINEERING PRIVATE LIMITED

B-21, Bhan Nagar, Queens Road, Jaipur-302021
 Website: www.aumshivay.com, www.omengineering.in

 E-mail:admin@aumshivay.com



Fall Arrester; Fall arrester on flexible anchor line is a device that automatically blocks and stops on the vertical support when the user falls. The anchor line can be a cable (flexible) or a rope (twisted or braided). These flexible anchor lines must be weighted with a counterweight. Breaking strength of these systems>15 kN. And We deals with the Guided type light weight Fall arrester are made up of Stainless Steel, have in built gravity lock to avoid incorrect use. These have two deliberate operation require to open and close. They are built in rope guided wheel for tangle free movement with anti panic features. They conforms the standards of EN353-2.

Specifications	
Description	Light weight guided type
Material	Stainless Steel.
Attachments	In built gravity lock to avoid incorrect use. Rope guided wheel for tangle free movement.
Strength	15 kN.
Standard	EN353-2



Applications:

- **Use:** It is used only in a job that requires significant amplitude of movements.
- Trades: The fall arrester on anchor line are mainly used for the following professions: works on pylons, Works on rock wall, works on lifts, window cleaner, rope access, rescue, roofer, roofing felt fixer.







B-21, Bhan Nagar, Queens Road, Jaipur-302021 Website: www.aumshivay.com, www.omengineering.in E-mail:admin@aumshivay.com

- How to choice? The choice of the fall arrest system must be based on the movement to perform.
 Obviously for the choice of the fall arrest system, the position of the anchor point must be considered.
 - If the movement is purely vertical (along a scale for example) we always favour a fall arrester on anchor line.
 - The fall arrester on anchor line must always be used directly below the anchor point.
 - For the work on an inclined plane with fall arrester on anchor line, it is necessary that it be equipped with a manual locking system.





TM